

C - Series



The most popular Pathport model. Suitable for flush-mounting, or for portable use.

FEATURES

- Two DMX512 ports, individually configurable
- DMX routing on a universe or channel-by-channel basis
- Multi-source merging or prioritizing
- Address up to 128 universes
- DMX output speed and signal loss behavior are user-selectable
- LCD display provides status feedback
- Uses Power-over-Ethernet (PoE) or an auxiliary 24VDC power supply (by others)
- Easily configured over the network
- RDM-compliant
- Fits a standard 2-gang, deep backbox
- Surface mount or portable enclosures available as accessories
- Elegant design suitable for any location
- Supports the following Ethernet protocols:
 - Strand Shownet
 - Pathport Protocol
 - ArtNet
 - E1.31 Streaming ACN (sACN/Net3)
 - ETC Net2 (output only)

MODEL DESCRIPTION

6201	Pathport C-Series Node with 2 - DMX inputs
6202	Pathport C-Series Node with 2 - DMX outputs
6203	Pathport C-Series Node with 1 DMX input, 1 DMX output

ACCESSORIES

6901	Surface Mount Enclosure
6911	Portable Enclosure - includes hanging bracket and Ethercon™ RJ45

Pathport Manager Configuration Software is available as a free download from our website



ten years of Pathport
www.pathwayconnect.com