



# Universal Colour Changer

## - The Same Great Reliability and Value in an Improved Design



With over 50,000 colour changers from the Chroma-Q™ range sold to date, it's no wonder they have an industry proven reputation for performance and reliability.

Combined with a choice of models to fit most fixtures and new advanced features, the range offers outstanding value.

The Chroma-Q Universal colour changer has been designed to maximise flexibility and usability by incorporating a host of next generation advanced features. Our integrated universal mounting system adjusts between 147-275mm and mounts fixtures with up to 50 degree beam angles without light loss. DMX control for fan speed, scrolling speed, gel-saver mode and reset is also incorporated. Requires additional power supply.

### Key Features

- ▶ 2 - 24 frames.
- ▶ Fits 500 - 2000W fixtures, with a lens of up to 203mm / 8" in diameter.
- ▶ Suitable for up to 50° beam angle (without light loss).
- ▶ Universal mounting system adjusts between 147 - 275mm / 6.8 - 10.8" and requires no additional mounting plates.
- ▶ DMX control for fan speed, scrolling speed, gel saver mode and reset.
- ▶ Highly reliable design.
- ▶ Rugged but lightweight construction.
- ▶ Easily accessible working components.
- ▶ Industry standard connectors.
- ▶ Fully compatible with other Chroma-Q models & accessories.
- ▶ Operation status indicators.
- ▶ Automatic self-calibration.
- ▶ Supplied with safety cable.

### Accessories

<b>PS02</b>	Chroma-Q 2PU DMX / Power Unit
<b>PS08</b>	Chroma-Q 8PU DMX / Power Unit
<b>MBPS12</b>	Chroma-Q Magic Box™ 12PU DMX / Power Unit
<b>GST16</b>	16 frame "Theatre" colour scroll
<b>GSR16</b>	16 frame "Rock & Roll" colour scroll
<b>ST</b>	High temperature clear scroll tape

Tourflex® Datasafe™ cable can be made to your specification.

### Universal Specification

<b>Product Code</b>	CHCQMU	<b>Frame Capacity</b>	2 - 24 frames
<b>Dimensions</b>	359mm x 345mm x 80mm / 14.1" x 13.6" x 3.1"	<b>Connectors</b>	XLR-4 (male) in & XLR-4 (female) through
<b>Weight</b>	2.5kg / 5.5lbs (inc. brackets)	<b>Power</b>	1.5PU (see separate PSU documentation)
<b>Aperture</b>	203mm x 260mm / 8" x 10.5"	<b>Control</b>	ANSI E1.1 DMX-512A

For the latest news and information on the Chroma-Q range, visit [www.chroma-q.com](http://www.chroma-q.com)